


CeLAN Touch Screen

DS-Ce-TS Rev A





The CeLAN Touch Screen provides a 5.7" Color LCD (liquid-crystal display) to provide the user with complete on-site system programming and operation control of the Protector System. The 5.7" Color LCD provides a graphical user interface to display visual status messages for the entire system. The display identifies any programmed location so the user can determine where an alarm, trouble, or open-sensor condition exists. Location names or zone/sensor text are displayed allowing for easy identification.



Features

- CeLAN AES encrypted technology for security, easy setup and enhanced performance
- 5.7" Color Touch Screen with protective display overlay and Lexan shield
- Simple, easy to use Graphical User Interface
- Four pass code entry options
- Scrambled/Standard QWERTY
- Scrambled/Standard 12-key Numeric
- Built-in 'on-line' help and diagnostic screens
- Remote keyboard option for use in programming using the CINCH-On PS2 Keyboard Interface.
- Two hardware input zones per module
- Five (5) state zones:
 - Open Circuit
 - Supervised Circuit (3k EOL)
 - Short Circuit
 - Ground Fault High
 - Ground Fault Low
- Surface or recessed mounting options.
- 'CINCH Stick' Field Upgradeable software



Open Zone Condition



Scrambled QWERTY Keyboard

CeLAN Touch Screen

Specifications

Power Requirements:

- Input: 12 VDC (8 VDC min, 14 VDC max)
- Output: N/A
- Current Draw: 240mA standby, 500mA max

Dimensions: 9.125" x 5." X 1.5" (LxWxD)

Environmental:

- Operation Temp: 32 to 120 F (0 to 49 C)
- Humidity: 90% relative humidity

Storage Temp:

- -30 to 140 F (-34 to 60 C)

Inputs:

- 2 hardwired supervised inputs

CELAN Devices per System:

- 100 CeLAN Devices

Listings:


- UL 1076
- FCC Part 15
- FIPS 197 Cert # 1125

Touch Screen Replacements




Touch Screen Assembly

RC-TS



Wall Mount



Wall Mount with conduit

Ordering

Control Panel

PCU-IDS Protector Panel

Touch Screen

Ce-TS Touch Screen
Ce-TS-P Plastic Touch Screen

Expansion Modules

Ce-2ZI 2 Zone Input
Ce-8ZI 8 Zone Input
Ce-4RO 4 Relay Output
Ce-24ZI 24 Zone Input

Communication Modules

Ce-FC-N Fiber Conversion
Ce-TCP/IP Network Module
Ce-FC-ER Fiber Conversion

CeLAN Modules

Ce-DS938Z Motion
Ce-DS308 Motion
Ce-DSISC Motion
Ce-M3ZS HSS L2 Contact
Ce-M1ZRS Recessed Contact
Ce-1076DRS Recessed Contact
Ce-1076HRS Recessed Contact
Ce-U1Z Universal 1 Zone
Ce-WF2ZI Wellsfargo Contact
Ce-U2Z Universal 2 Zone

Receivers

Ce-AESR-IDS AES Receiver

CeLAN Accessories

CO-CSU Cinch Stick
CO-PS2KI Keyboard Module
CO-T-P Panel Tester
CO-T-8Z 8 Zone Tester
CO-T-4R 4 Relay Tester
CO-T-Printer Printer Tester
CO-PRSI Siren Supervision
Ce-EX Expansion Module

Power

ACC-T24V-100 Transformer
ACC-B12-18 18Ahr Battery
ACC-B12-7 7Ahr Battery
ACC-6P Power Cord
E-CB Termination Box

Accessories

L-M-KD Panel Lock
L-M-KA Panel Lock
ACC-CFC-S Fiber Cable
L-S Standard Panel Lock
ACC-CFC-MM Fiber Cable
S-ET Panel Tamper

Enclosures

E-P Panel Enclosure
E-P-Kit
E-CP Plastic Enclosure
E-PA Accessory Enclosure
E-PA-Kit
E-PA-S Small Accessory Enclosure
E-PA-S-Kit

For more information: www.cinchsystems.com

Cinch Systems

10275 43rd St NE, Ste 300

St Michael, MN 55379

1-763-497-1059

