

uplink[®] CDMAEZ



Universal Alarm Communicator

For Primary or Redundant Alarm Communications

The Uplink[®] CDMAEZ includes the latest technology for the best performance and longest life cycle. Compatible with CDMA cellular networks, The CDMAEZ is designed as a summary event communicator.

The Uplink CDMAEZ communicates to central stations by dialup to any industry standard receiver, or over the internet to an IP receiver—all with the exceptional service and features you've come to expect from Uplink, the leading supplier of wireless security solutions.

Uplink Value:

Supports virtually all security systems and multiple formats

Perfect for residential alarm systems

Flat-rate billing for improved dealer profitability

Customizable product marketing services through a simple e-commerce website

Live technical and activation support 8:00 a.m. to 8:00 p.m. EST, Monday through Friday

Remote on-demand testing for status and signal strength with UplinkInstaller™



Supports Uplink Remote for Interactive Control

- ✓ "Out-of-the-box" operation — no special programmer or central station equipment is required
- ✓ Universal cellular communications, for summary event reporting
- ✓ Power from the panel or separate 12V DC power supply
- ✓ Two programmable outputs
- ✓ Supports Uplink Remote™, momentary or latching keyswitch zones, no adapter board required
- ✓ Login @ uplinkremote.com for remote arming and disarming
- ✓ Installs in minutes with complete end-to-end signal verification
- ✓ Contact ID, SIA, pulse 4/2 (:20 PPS) and modem II/IIIa²
- ✓ Smart siren bell sampling to detect burglary or fire condition



Uplink Commitment

Uplink products deliver the unique combination of technology, quality, options and superior value that has made Uplink the security industry's most trusted source for alarm communicators since 1996.

With hundreds of thousands of installed communicators throughout the United States and Canada, Uplink has the experience and expertise to provide the most reliable products and the finest support.

Plus, Uplink wireless communicators are backed by the unique combination of the proprietary ISO-27001 certified network service offering and an advanced dealer support web management tool.

For more information, visit the Uplink website dealer portal at uplink.com.

Technical Specifications

INPUTS	
Four Inputs	<ul style="list-style-type: none"> Input 1: Connect to siren/bell (distinguishes between burg/steady and fire/pulsed) or programmable to 12 volts Inputs 2-4: 12 volts
OUTPUTS AND REPORTING	
Central Station	<ul style="list-style-type: none"> Contact ID, SIA, Pulse 4/2 (:20 PPS) and modem II/IIIa² Internet or dial-up
Relay Outputs	Two-configurable
Other Reporting	<ul style="list-style-type: none"> Low voltage Email alerts to customer or alarm company
Testing	<ul style="list-style-type: none"> Weekly or daily
Status LEDs	<ul style="list-style-type: none"> Signal Strength Network Service Communications
POWER SOURCE – NOT INCLUDED	
Power Requirements	<ul style="list-style-type: none"> 12V DC 500 mA max on transmit 28mA standby
RADIO	
CDMA	Compatible with CDMA networks
Cellular Frequencies	850/1900 MHz
Transmit Power	Maximum allowable: <ul style="list-style-type: none"> 1.0W at 1900 MHz 2.0W at 850 MHz
OPTIONAL ACCESSORIES	
Magnet mount antenna with 9ft cable - part number 1004ANT 8 inches tall high gain antenna with articulating joint - part number 1005ANT	
DIMENSIONS	
Height/Width/Depth (inches)	4.75/3.3/1.3
Antenna	3.75 inches